

Claim Listing

Please amend the claims as follows and add the following new claim 15.

1. (currently amended) A process of ~~spatially encoding~~ separating and then merging distinct groups of particles in a planar assembly of particles which is formed on a substrate by sequential injection of a multiplicity of groups of particles of at least one type, said process comprising:
providing a substrate comprising a light-sensitive planar electrode, the light-sensitive electrode being aligned with another planar electrode in substantially parallel arrangement, with said electrodes being separated by a gap, and the gap containing an electrolyte solution which is in contact with said electrodes;
placing a group of at least one type of particles selected from a reservoir containing said at least one type of particles into the electrolyte solution so as to confine said injected particles into a first distinct segment of the light-sensitive electrode, wherein the first distinct segment is illuminated by an illumination source to delineated by a first distinct illumination pattern on said light-sensitive electrode;
translocating said confined particles to ~~a second~~ another distinct segment of the light-sensitive electrode, wherein said another distinct segment is illuminated by an illumination source to delineated by another second distinct illumination pattern on said light-sensitive electrode, wherein said second another distinct segment either has no particles in it or has a planar assembly of particles in it; and
merging said translocated particles with any ~~pre-existing planar assembly of particles previously formed~~ in said ~~second~~ another distinct segment of the light-sensitive electrode.
2. (previously presented) The process of claim 1, further comprising recording an image showing said translocated groups of particles in their final positions within said second segment.
3. (currently amended) The process of claim 2, wherein the first illumination pattern and the second illumination pattern are provided using a programmable illumination pattern generator which can be selectively activated to generate said illumination patterns, said method further comprising reiterating the placing, translocating, merging and recording steps n times, wherein n is an integer from zero to about 10,000.

4. (currently amended) A process of decoding a planar assembly of particles generated and encoded according to the process of claim 3, said decoding by a process comprising: providing a substrate comprising a light-sensitive planar electrode, the light-sensitive electrode being aligned with another planar electrode in substantially parallel arrangement, with said electrodes being separated by a gap, and the gap containing an electrolyte solution which is in contact with said electrodes; placing a group of at least one type of particles selected from a reservoir containing said at least one type of particles into the electrolyte solution so as to confine said injected particles into a first segment of the light-sensitive electrode, wherein the first segment is illuminated by an illumination source controlled by a programmable illumination pattern generator to delineate a first illumination pattern on said light-sensitive electrode, and recording an image of the substrate; translocating said confined particles to another distinct segment of the light-sensitive electrode, wherein said another distinct segment is illuminated by an illumination source controlled by the programmable illumination pattern generator to delineate second illumination pattern on said light-sensitive electrode, wherein said another distinct segment either has no particles in it or has a planar assembly of particles in it, and recording an image of the substrate; merging said translocated particles with any particles in said another distinct segment of the light-sensitive electrode thereby forming an array of merged particles, the composition of which is encoded based on its location on the substrate, and recording an image of the substrate; and comparing the images taken following each of the placing, translocating and merging steps in order to decode the composition of the array of merged particles.
~~cross-correlating an image of the planar assembly with each of the images recorded at the completion of each placing, translocating and merging step.~~

5. (canceled) A self-tuning filter comprising:

a light-sensitive planar electrode that is aligned with another planar electrode in substantially parallel arrangement, with said electrodes being separated by a gap, and the gap containing an electrolyte solution which is in contact with said electrodes and which contains colloidal particles, wherein said particles are assembled in a planar array on the

light-sensitive electrode, said array being composed so as to partially block incident light that controls array assembly in response to an electric field, and wherein the lateral density of said array self-adjusts in response to transmitted light intensity;

means for adjusting frequency of said applied electric field to a value lower than the characteristic dielectric relaxation frequency of said particles;

means for defining an illuminated area on said light-sensitive electrode; and

means for adjusting illumination intensity so as to induce assembly of said particles within the illuminated area.

6. (canceled) The self-tuning filter of claim 5, wherein self-adjustment determines an optimal lateral density on attaining equilibrium which correlates with the transmitted light intensity of the frequency of the applied electric field.

7. (canceled) A fractionation device for spatially separating and sorting a mixture of particles on a substrate comprising:

a substrate comprising a light-sensitive planar electrode, the light-sensitive electrode being aligned with another planar electrode in substantially parallel arrangement, with said electrodes being separated by a gap, and the gap containing an electrolyte solution which is in contact with said electrodes and which contains colloidal particles suspended in the electrolyte solution, said particles comprising a multiplicity of particle types exhibiting a differential frequency-dependent response to an applied electric field in accord with the respective characteristic frequency of each said particle type;

means for applying a time-varying voltage between said electrodes so as to generate a time-varying electric field and to induce the motion of said particles;

a means for adjusting frequency to a value less than the characteristic frequency of at least one particle type; and

a light-control component permitting illumination of a predetermined segment of the substrate with a predetermined intensity so as to induce collection into said illuminated segment of substantially all said particles of said at least one particle type having respective characteristic frequencies exceeding the frequency of the applied field.

8. (canceled) The fractionation device of claim 7, wherein the particles are cells.

9. (canceled) The fractionation device of claim 7, wherein the light-controlled component

is a programmable illumination pattern generator.

10. The fractionation device of claim 7, wherein the particles may be collected into an illuminated segment being laterally scanned or reconfigured.

11. (canceled) The fractionation device of claim 7, wherein the particles are separated based on differential-frequency response determined by particle size or by particle chemical composition.

12. (canceled) A flow control device for generating fluid flow comprising:

- a light-sensitive planar electrode that is aligned with another planar electrode in substantially parallel arrangement, with said electrodes being separated by a gap, and the gap containing a fluid medium that is in contact with said electrodes;

- means for applying a time-varying voltage between said electrodes so as to generate a time-varying electric field and to induce said fluid medium to undergo lateral flow;

- means for adjusting voltage magnitude and frequency to preselected values to control flow velocity; and

- a light-control component permitting illumination of a designated segment of the light-sensitive electrode, the combination of said time-varying electric field and illumination producing transverse fluid flow in accordance with the contour shape of the illuminated segment, said flow having a velocity component everywhere directed parallel to the surface and normal to the contour.

13. (canceled) The flow control device of claim 12, said device being operated to generate a sequence of flow configurations.

14. (canceled) The flow control device of claim 12, said device being operated so as to produce local flow fields in a configuration effecting the mixing of the fluid medium.

15. (newly added) The process of claim 1 further including the step of:

- placing an additional group of at least one type of additional particles selected from a reservoir containing said at least one type of additional particles into the electrolyte solution so as to confine said injected additional particles into a third segment of the light-sensitive electrode delineated by a third illumination pattern on said light-sensitive electrode;

translocating said confined additional particles to the second segment of the light-sensitive electrode; and
merging said additional particles with any particles in said second segment of the light-sensitive electrode.